



Replace your old
PVC enclosure with
new Fibox Tempo -
now it is easy!

FIBOX[®] TEMPO



- Dimensions and mounting pods compatible with market standards
- Low base makes installation easy
- Rapid hinges can be installed in seconds, no tools or screws needed
- Several wall mounting options
- Large plain cover for printing, labels and switches
- Variety of accessories

Now it is easy to change your old box to high-quality Fibox, because Tempo - product family is fully compatible with common PVC boxes. Fibox Tempo is designed to save your time and costs. Try now!

Fibox
Website: www.fibox.co.uk
E-mail: sales@fibox.co.uk
Tel (+44) 1642 604 400
Fax (+44) 1642 604 600

FIBOX[®]
Enclosing innovations



For SLI: enter 14052 at www.tim-info.com/ien

Coating

highly corrosion resistant



The corrosion resistance of the very hard Lunac 2+ coating is particularly long lasting because unique compressive stresses keep it micro crack free. The coating is well-suited for use in hydraulic systems thanks to its high hardness, anti-cold weld properties and welding quality to the substrate. Lunac 2+ coatings are finished with a roughness of Ra=0.12-0.3µm and do not need any post treatment.

WMV
Tel. +31-548-520681
Fax +31-548-513407
For SLI: enter 13986
at www.tim-info.com/ien

Steel Cable Carriers

lightweight, yet robust

The LS 1050 and LSX 1050 steel chains combine the light weight of plastic with the strength of steel. This



has been made possible thanks to a consistently weight-optimised design which are roughly 40 per cent lighter than before. High additional loads, greater acceleration and travel speeds are now possible with greater unsupported lengths. A wide range of separation options with dividers and height subdivisions is available. The C-rail required for attaching the strain relief elements is fixed using a holder in the connectors, and does not need to be screwed on separately.

KABELSCHLEPP
Tel. +49-271-58010
Fax +49-271-5801220
Enter 13906 at www.tim-info.com/ien

Digital Counters

IP65 rating, require no setup

The FKA03-Counter provides an uncomplicated method of counting from 0 up to 99,999,999 and is suitable for use wherever slow counting is required. The device is operational from -10 up to 55°C, with the input voltage range expanded from 10 to 260VAC/DC enabling a maximum count frequency of 30Hz. FKA03 measures 24 x 48mm and features a highly visible eight digit large character LCD for easy reading. The built-in long life lithium battery gives up to eight years continuous use. Additional features include a front reset button with locking function for fast and easy counting reset. The front is sealed to IP65.



CARLO GAVAZZI
Tel. +39-02-931761
Fax +39-02-93176301
Enter 13991 at www.tim-info.com/ien

Laser-Distance Sensor

with a precision of 1.5mm



The new DLS-B optical measuring device can measure absolute distances up to 500m with a precision of 1.5mm. It represents a cost efficient solution even at extreme environment temperatures as low as -40°C. Serial, analogue and digital interfaces are standard features enabling you to easily connect the DLS-B to a control system (SPS, IPC or PC). The device measures distances on natural and reflective surfaces and determines positions of objects with difficult access or high surface temperatures.

DIMETIX
Tel. +41-71-3832010
Fax +41-71-3832011
Enter 13977 at www.tim-info.com/ien

Industrial Beacons

IP65, 10 and 24J units available

The Flashguard range of electronic sounders and beacons has been expanded with the introduction of high intensity industrial xenon beacons. Available in either 10 or 24J units, the beacons feature Fresnel lenses producing a penetrating light, and has single or double flash settings. All the beacons are sealed to IP65 and come with a choice of red, amber, blue, green and clear lenses. A range of accessories is available, including protective cage guards and wall brackets. A soft start unit is also available for the 24J beacon which operates on 24VDC.



KLAXON SIGNALS
Tel. +44-161-2875555
Fax +44-161-2875511
Enter 14014 at www.tim-info.com/ien

Gauge

for humidity and temperature

The Humiport 05 provides precise mobile measurements of relative humidity and temperature in the ranges of 5...95% RH and -20...50°C. Furthermore dew point, absolute humidity and mixing ratio are shown on the easily readable display. With the compact dimensions of a mobile phone, the Humiport 05 offers easy handling with the proven thumb-wheel switch. Measured values can be displayed as SI- or as US-units, and features such as MIN/MAX, AVG and HOLD functions are provided.



E + E ELEKTRONIK
Tel. +43-7235-60530
Fax +43-7235-6058
Enter 13971 at www.tim-info.com/ien

Torque Limiters | **Bellow Couplings** | Miniature Couplings | Elastomer Couplings | Line Shafts | Linear Couplings

ECONOMIC MIRACLE.

BACKLASH-FREE, TORSIONALLY RIGID, PRICED TO MOVE.



R+W[®]
COUPLING TECHNOLOGY

THE ULTIMATE COUPLING.
FROM 0.1 TO 10,000 NM.

R+W Antriebselemente GmbH | Phone: +49 93 72-98 64-0 | E-Mail: info@rw-kupplungen.de | Internet: www.rwcouplings.com

For SLI: enter 11745 at www.tim-info.com/ien